

SAFETY DATA SHEET

Product name: MaxPox® 60 Hardener

Issue Date: 03/08/2016

Print Date: 05/01/2016

MaxLiner encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: MaxPox 60 Hardener

Recommended use of the chemical and restrictions on use

Identified uses: Hardener for epoxy resin.

COMPANY IDENTIFICATION

MAXLINER

450 COLLEGE DRIVE

MARTINSVILLE, VA 24112 USA

Customer Information Number: +1 877-426-5948, Email: info@maxlinerusa.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: (Infotrac) 800-535-5053

Local Emergency Contact: 800-535-5053

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Acute toxicity - Category 4 - Oral

Skin corrosion - Category 1B

Serious eye damage - Category 1

Skin sensitization - Category 1

Reproductive toxicity - Category 1B

Effects on or via lactation

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Harmful if swallowed.

Causes severe skin burns and eye damage.
 May cause an allergic skin reaction.
 May damage fertility or the unborn child.
 May cause harm to breast-fed children.

Precautionary statements

Prevention

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 Avoid contact during pregnancy/ while nursing.
 Wash skin thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Contaminated work clothing should not be allowed out of the workplace.
 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
 IF exposed or concerned: Get medical advice/ attention.
 If skin irritation or rash occurs: Get medical advice/ attention.
 Wash contaminated clothing before reuse.

Storage

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	10.0 – 30.0%
Triethylenetetramine mixture	112-24-3	25.0 – 30.0%
Aminoethylethanolamine	111-41-1	<0.4%
Tetraethylenepentamine mixture	112-57-2	<0.2%
3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine)	2855-13-2	30.0 – 50.0%
Benzyl alcohol	100-51-6	7.0 – 13.0%

Note

Liquid Epoxy Resins (LERs) are made by reacting bisphenol A and epichlorohydrin. Olin uses both CAS No. 25085-99-8 and 25068-38-6 for its LERs. Other manufacturers use CAS No. 25068-38-6 for their LERs. Accordingly, LER manufacturers consider that derivatives of LERs may be described using either CAS number as a starting material.

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Immediate continued and thorough washing in flowing water for at least 30 minutes is imperative while removing contaminated clothing. Prompt medical consultation is essential. Wash clothing before reuse. Properly dispose of leather items such as shoes, belts, and watchbands. Items which cannot be decontaminated, including leather articles such as shoes, belts, and watchbands should be disposed of properly. Suitable emergency safety shower facility should be immediately available.

Eye contact: Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: Do not induce vomiting. Give one cup (8 ounces or 240 ml) of water or milk if available and transport to a medical facility. Do not give anything by mouth unless the person is fully conscious.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. May cause asthma-like (reactive airways) symptoms. Bronchodilators, expectorants, antitussives and corticosteroids may be of help. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Chemical eye burns may require extended irrigation. Obtain prompt consultation, preferably from an ophthalmologist. If burn is present, treat as any thermal burn, after decontamination. Due to irritant properties, swallowing may result in burns/ulceration of mouth, stomach and lower gastrointestinal tract with subsequent stricture. Aspiration of vomitus may cause lung injury. Suggest endotracheal/esophageal control if lavage is done. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Carbon dioxide. Carbon monoxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately

withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Evacuate area. Only trained and properly protected personnel must be involved in clean-up operations. Keep upwind of spill. Ventilate area of leak or spill. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Sand. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get in eyes, on skin, on clothing. Do not swallow. Avoid breathing vapor. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Store in a cool, dry place.

Storage stability

Storage temperature:	Shelf life: Use within
0 - 30°C (32-86°F)	12 month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of Listing	Value/Notation
Triethylenetetramine mixture	US WEEL US WEEL	TWA TWA	1 ppm Absorbed via skin
Aminoethylethanolamine	Dow IHG	TWA	0.06 mg/m3
Tetraethylenepentamine	US WEEL	TWA	5 mg/m3
Benzyl alcohol	US WEEL US WEEL	TWA TWA	SKIN, DSEN 10 ppm

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Avoid gloves made of: Polyvinyl alcohol ("PVA"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES**Appearance**

Appearance	
Physical state	Liquid
Color	Yellow
Odor	Amine
Odor Threshold	No test data available
pH	12 <i>Literature</i>
Melting point/range	Not applicable
Freezing point	-35°C (-31°F) <i>Literature</i>
Boiling point (760 mmHg)	277°C (531°F) <i>Literature</i> Diethylenetriamine
Flash point	Closed cup >148°C (298°F) <i>Literature</i>
Evaporation Rate (Butyl Acetate =1)	No test data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	<0.01 kPa at 20°C (68°F) <i>Literature</i>
Relative Vapor Density (air=1)	5 at 20°C (68°F) <i>Literature</i>
Relative Density (water=1)	0.97 <i>Literature</i>
Water solubility	100% at 20°C (68°F) <i>Literature</i>
Partition coefficient: n-octanol/water	This product is a mixture. See Section 12 for individual component data
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Dynamic Viscosity	200 cP at 25°C (77°F) <i>Literature</i>
Kinematic Viscosity	700 cSt at 25°C (77°F) <i>ASTM D 445</i>
Explosive properties	No
Oxidizing properties	No
Molecular weight	No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Reaction with carbon dioxide may form an amine carbamate. Smoke may be generated depending on vapor pressure of mixture. Product absorbs carbon dioxide from the air.

Incompatible materials: Avoid contact with oxidizing materials. Avoid contact with: Acids. Acrylates. Alcohols. Aldehydes. Halogenated hydrocarbons. Ketones. Nitrites. Avoid contact with metals such as: Brass. Bronze. Copper. Copper alloys. Avoid contact with absorbent materials such as: Ground corn cobs. Moist organic absorbents. Peat moss. Sawdust.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aromatic compounds. Ammonia. Ethylenediamine. Volatile amines. Hydrocarbons. Phenolics.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Swallowing may result in gastrointestinal irritation or ulceration. Swallowing may result in burns of the mouth and throat.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 1,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, Rabbit, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; vapor from heated material may cause adverse effects. Excessive exposure may cause severe irritation to upper respiratory tract (nose and throat) and lungs.

The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause severe skin burns. Symptoms may include pain, severe local redness and tissue damage.

Serious eye damage/eye irritation

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

Sensitization

For skin sensitization:

A component in this mixture has caused allergic skin reactions in humans.

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

Individuals having an allergic skin reaction to this product may have an allergic skin reaction to similar material(s).

The similar material(s) is/are:

Ethylenediamine.

Triethylenetetramine (TETA).

Piperazine.

Aminoethylethanolamine (AEEA).

Aminoethylpiperazine (AEP).
For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Material is corrosive. Material is not classified as a respiratory irritant; however, upper respiratory tract irritation or corrosivity may be expected.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals:
lung
Respiratory tract.
Central nervous system.
Muscles.
Urinary tract.

Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

Teratogenicity

Contains component(s) which caused birth defects in laboratory animals. Contains component(s) which have been toxic to the fetus in lab animal tests.

Reproductive toxicity

In an oral gavage screening study, DETA has been toxic to the fetus in laboratory animal tests. Contains component(s) which have interfered with fertility in animal studies.

Mutagenicity

Contains component(s) which were positive in in vitro genetic toxicity studies. Genetic toxicity studies in animals were negative for component(s) tested.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:**Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers****Acute inhalation toxicity**

The LC50 has not been determined.

Triethylenetetramine mixture**Acute inhalation toxicity**

The LC50 has not been determined.

Aminoethylethanolamine**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility; vapor from heated material may cause respiratory irritation. Based on the available data, narcotic effects were not observed.
The LC50 has not been determined.

Tetraethylenepentamine mixture**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility. Excessive exposure may cause irritation to upper respiratory tract (nose and throat).
The LC50 has not been determined. Rat, 8 Hour, vapour, No deaths occurred following exposure to a saturated atmosphere.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine)**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 5.01 mg/l

Benzyl alcohol**Acute inhalation toxicity**

LC50, Rat, 4 Hour, vapour, 11 mg/l

12. ECOLOGICAL INFORMATION*Ecotoxicological information appears in this section when such data is available.***Toxicity****Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 2 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1.8 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Scenedesmus capricornutum (fresh water algae), static test, 72 Hour, Growth rate inhibition, 11 mg/l

Toxicity to bacteria

IC50, Bacteria, 18 Hour, Respiration rates., > 42.6 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 0.3 mg/l

MATC (Maximum Acceptable Toxicant Level), Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 0.55 mg/l

Triethylenetetramine mixture**Acute toxicity to fish**

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

May increase pH of aquatic systems to > pH 10 which may be toxic to aquatic organisms.

LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 330 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 31.1 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), semi-static test, 72 Hour, Growth rate inhibition, 20 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, 680 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 1.9 mg/l

Aminoethylethanolamine**Acute toxicity to fish**

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), 96 Hour, 640 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

Acute toxicity to algae/aquatic plants

ErC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate inhibition, 353.6 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 5,000 mg/l

Tetraethylenepentamine mixture

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

May increase pH of aquatic systems to > pH 10 which may be toxic to aquatic organisms.

LC50, Poecilia reticulata (guppy), semi-static test, 96 Hour, 420 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 24.1 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth rate inhibition, 6.8 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, activated sludge, static test, 1 Hour, 1,600 mg/l

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine)

Acute toxicity to fish

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Leuciscus idus (Golden orfe), semi-static test, 96 Hour, 110 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 23 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

EbC50, alga Scenedesmus sp., 72 Hour, Biomass, 37 mg/l

Toxicity to bacteria

EC10, Bacteria, Static, 18 Hour, 1,120 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 3 mg/l

Benzyl alcohol

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), Static, 96 Hour, 460 mg/l, Method Not Specified.

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 230 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), Static, 72 Hour, Growth rate, 770 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, activated sludge, Respiration inhibition, 49 Hour, Respiration rates., 2,100 mg/l, OECD 209 Test

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna, semi-static test, 21 d, 51 mg/l

Persistence and degradability**Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers**

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Not applicable

Biodegradation: 12 %

Exposure time: 28 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 2.35 mg/mg Estimated.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 1.92 Hour

Method: Estimated.

Triethylenetetramine mixture

Biodegradability: Biodegradation under aerobic static laboratory conditions is moderate (BOD20 or BOD28/ThOD between 10 and 40%).

10-day Window: Fail

Biodegradation: 0 %

Exposure time: 20 d

Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand: 3.40 mg/mg

Chemical Oxygen Demand: 1.94 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	5.000%
20 d	2.5 – 11%

Aminoethylethanolamine

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: > 97 %

Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

Theoretical Oxygen Demand: 2.77 mg/mg

Chemical Oxygen Demand: 1,070 mg/g

Tetraethylenepentamine mixture

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

10-day Window: Fail
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301A or Equivalent
 10-day Window: Not applicable
Biodegradation: 17 %
Exposure time: 84 d
Method: OECD Test Guideline 302A or Equivalent
Theoretical Oxygen Demand: 3.39 mg/mg
Chemical Oxygen Demand: 1.54 - 1.88 mg/mg
Biological oxygen demand (BOD)

Incubation Time	BOD
20 d	0 – 12%

Photodegradation
Atmospheric half-life: 0.41 Hour
Method: Estimated.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine)

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.
 10-day Window: Fail
Biodegradation: 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301A or Equivalent
 10-day Window: Not applicable
Biodegradation: 42 %
Exposure time: 3 Hour
Method: OECD Test Guideline 303A or Equivalent
Theoretical Oxygen Demand: 3.38 mg/mg
Photodegradation
Test Type: Half-life (indirect photolysis)
Sensitizer: OH radicals
Atmospheric half-life: 0.126 d
Method: Estimated.

Benzyl alcohol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
 10-day Window: Not applicable
Biodegradation: 92 - 96 %
Exposure time: 14 d
Method: OECD Test Guideline 301C or Equivalent
Theoretical Oxygen Demand: 2.52 mg/mg
Photodegradation
Test Type: Half-life (indirect photolysis)
Sensitizer: OH radicals
Atmospheric half-life: 1.296 d
Method: Estimated.

Bioaccumulative potential

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).
Partition coefficient: n-octanol/water(log Pow): 3.242 at 25 °C Estimated.

Triethylenetetramine mixture

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -2.65 Estimated.

Aminoethylethanolamine

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -1.46 Measured

Bioconcentration factor (BCF): < 3.7 Cyprinus carpio (Carp) 42 d Measured

Tetraethylenepentamine mixture

Bioaccumulation: No bioconcentration is expected because of the relatively high water solubility.

Partition coefficient: n-octanol/water(log Pow): -3.16 Estimated.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine)

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.79 Measured

Benzyl alcohol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.10 Measured

Mobility in soil**Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers**

Potential for mobility in soil is low (Koc between 500 and 2000).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 1800 - 4400 Estimated.

Triethylenetetramine mixture

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 4.1 - 310 Estimated.

Aminoethylethanolamine

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 3.5 Estimated.

Tetraethylenepentamine mixture

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 3.6 - 1098 Estimated.

3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine)

Potential for mobility in soil is medium (Koc between 150 and 500).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 340 Estimated.

Benzyl alcohol

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 16 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Amines, liquid, corrosive, n.o.s.(3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine), Triethylenetetramine mixture)
UN number	UN 2735
Class	8
Packing group	II

Classification for SEA transport (IMO-IMDG):

Proper shipping name	Amines, liquid, corrosive, n.o.s.(3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine), Triethylenetetramine mixture)
UN number	UN 2735
Class	8
Packing group	II
Marine pollutant	Epoxy resin
Transport in bulk according to Annex I or II or MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Amines, liquid, corrosive, n.o.s.(3-Aminomethyl-3,5,5-trimethylcyclohexylamine (isophoronediamine), Triethylenetetramine mixture)
UN number	UN 2735
Class	8
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard
Chronic Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Triethylenetetramine mixture	112-24-3
Benzyl alcohol	100-51-6

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION**Hazard Rating System****NFPA**

Health	Fire	Reactivity
3	1	0

Revision

Identification Number: 101215965 / A476 / Issue Date: 03/08/2016 / Version: 8.0

Legend

Absorbed via skin	Absorbed via skin
Dow IHG	Dow Industrial Hygiene Guideline
SKIN, DSEN	Absorbed via Skin, Skin Sensitizer
TWA	8-hr TWA
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

MAXLINER urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.