

SpeedyLight+

A Single Light Cure Platform for 2"-24"

DESCRIPTION

The SpeedyLight+ LED curing system is a game changer in the sewer renovation market. Its revolutionary LED technology allows contractors to optimize their operations by increasing working efficiency at the job site up to six times. It is designed to cure felt liners, invertible glass-fiber liners and fibre-glass pull-in liners.

SpeedyLight+ works in dn 2" | 50mm up to dn 24" | 600mm with different configurations of curing heads. Compatible with felt liners and GRP UV liners. Also compatible with our SpectraDive curing head for manhole rehabilitation. SpeedyLight+ can also do point-repair with our family of LED packers.

PRODUCT INFORMATION

- **Dimensions (LxWxH):** 58" x 21" x 36" | 1473mm x 533mm x 914mm
- **Total Weight:** 282 lbs | 128 kg
- **Material:** Chassis based on aluminium, stainless steel and ABS
- **HMI:** 9.7" | 246.38mm Touch Panel
- **PLC:** Siemens Simatic
- **Main Monitor:** 10" | 254mm installed within the CU
- **Auxiliary Monitor:** 7" | 178mm installed within the PU
- **Wi-Fi Connectivity:** 2.4 GHz
- **Mode:** AP
- **Internal Access:** Socek RJ45, WAN, Mobile tethering via USB

SAFETY

- **Auto-stop Function:** Yes, by sensor of contact
- **Emergency Stop:** Yes, Emergency Stop Button installed within the CU
- **Power:** RCD Switch

POWER REQUIREMENTS

- **Voltage:** 110-230V 50/60 Hz
- **Mains Requirement:** E-type or std. Schuko wall socket
- **Connection:** 16 ft | 5m power cord
- **Power:** 8.5A 220V / 17A 110V

CABLE REEL

- **Umbilical Cable:** Option: 164 ft | 50m, 230 ft | 70m, 328 ft | 100m

